

This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987. The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

ESD Analysis



Prepared For: KX Architecture Pty Ltd

Project: Development of 4 residential dwellings

Address: 8 Carpenter Street, Noble Park

Reference Number: 202405

Date: 23rd January 2024

Prepared by: Geokal Services Pty Ltd



CONTENTS

This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

2 – Building Description

3 – Documentation Reviewed Page 5

4 – Assessment Methods Page 5

5 – Limitations Page 5

6 – Findings & Results Page 5

 6.1 – Building Fabric Page 5

 6.2 - External Glazing Page 6

 6.3 - Building Sealing Page 7

 6.4 - Air Movement Page 7

 6.5 - Services Page 7

 6.6 - Artificial Lighting and Power Page 7

 6.7 – NathERS Assessment Outcomes Page 9

 6.8 – BESS Assessment Outcomes & ESD Principles Page 9

7 – Conclusion Page 13

Appendix 1 – Sustainable Management Plan Page 14

Appendix 2 – Individual FirstRate Ratings Page 28


Appendix 3 – STORM Assessment & Selection of Plants Page 31

Appendix 4 – Additional Construction Consideration Page 33

PREPARED BY: Geokal Services Pty Ltd

PROJECT: Development of 4 residential dwellings

AUTHOR: George Kalajdzic (DMN/11/2035)

SIGNED: 

Revision	Issue	Date
-	First issue	23 rd January 2024

This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

1. SCOPE

The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

The BESS assessment has also been included as part of this report.

2. **BUILDING DESCRIPTION**

2.1. The proposed building consists of construction of 4 residential dwellings. Some building characteristics which are to be noted are as follows:


Climate Zone: Melbourne (Zone 6)

Direction of Heat Flow: Upwards

Roof Lights: Non-Applicable

Class of Building: 1a (Dwelling)


Proposed development is located at 8 Carpenter Street, Noble Park. The proposed building site location is suburban and is surrounded by existing residential buildings and landscaping which provide some protection from the elements. The image along with the architectural drawings gives a clear indication of the above.




This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987. The following plans were used during this purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

68

GROUND FLOORPLAN



FIRST FLOORPLAN



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

3. DOCUMENTATION REVIEWED
The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

4. ASSESSMENT METHOD
4.1. This report has been prepared using FirstRate5 version 5.2.3 and The BESS program has been used in addressing the above objectives. No additional software has been used during this assessment.

5. LIMITATIONS

5.1. This report is to be strictly used as a verification method of the proposed building and is not to be used for any of the following;

- Used in validation or reference to any other building which are not nominated in this report,
- Used in validation of any heating or cooling services and systems.


6. FINDINGS AND RESULTS

6.1. Section 3.12.1 - Building Fabric:

6.1.1. Building insulation requirements are as follows below;

ASSEMBLY	#MINIMUM INSULATION	LOCATION
*CEILING	R6.0	
WALLS	R2.5	
WALLS (Double for part walls)	R2.5	
FLOOR	R2.5	
UNDERSLAB INSULATION	R1.5	


GROUND FLOORPLAN



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

FIRST FLOORPLAN



Section 3.12.2 – External Glazing:

6.1..1.1. An assessment of the proposed glazing as nominated on the drawings has been taken into consideration as part of this energy rating assessment.;

WINDOW TYPE	Window Type	MINIMUM U-VALUE	MINIMUM SOLAR HEAT GAIN COEFFICIENT (SHGC)	LOCATION
Aluminium double glazed	Sliding Doors, fixed windows	U Value = 3.6	SHGC = 0.54	Townhouse 1, 2 & 3
	Awning Windows	U Value = 3.6	SHGC = 0.47	

6.2. Section 3.12.3 – Building Sealing:

6.2..1.1. Building sealing procedures are to be as following:

- All roofs, walls, floors etc are to be constructed in a manner that will minimise airleakage and all doors and windows are to be adequately sealed by foam or rubber materials to prevent any air infiltration, and
- All exhaust fans, flues, evaporative coolers, or any other mechanical ventilation/temperature control systems are to be provided with self closing dampers or flaps that will seal and prevent any air infiltration.



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

6.3. Section 3.12.4 – Air Movement:

The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purposes specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

6.3.1.1. Air movement has been assessed as part of FirstRate assessment and has been taken into consideration as part of this star rating. Air movement is to comply with the requirements of BCA part F4. The relevant building surveyor is to assess and approve the proposed building to BCA Part F4. A part F4 will ensure compliance with BCA part 3.12.4.

6.4. Section 3.12.5 – Service:

6.4.1.1. No heating or cooling services have been considered as part of this FirstRate/Part 3.12 assessment.

Plans/specifications are to make reference to the following service insulation procedures for any new ducted heating:

Service Unit	Insulation Location	Minimum R-Value of Insulation to be installed	Insulation Type
Central Heating (water pipes only)	Internal piping	0.2	9mm of closed cell polymer – or similar
	Piping located in ventilated wall space, enclosed sub-floor or roof space	0.45	19mm of closed cell polymer – or similar
	Piping located external to the building or unenclosed subfloor or roof space	0.6	25mm of closed cell polymer – or similar
Evaporative cooling systems	Ductwork	0.6	40mm polyester fibre insulation (250g/m ²) – or similar
	Fittings	0.4	40mm polyester fibre insulation (250g/m ²) – or similar
Heating only or refrigerated cooling only systems	Ductwork	1	70mm polyester fibre insulation (450g/m ²) – or similar
	Fittings	0.4	40mm polyester fibre insulation (250g/m ²) – or similar
*See Note			
Combined heating and refrigeration cooling systems	Ductwork	1.5	90mm polyester fibre insulation (800g/m ²) – or similar
	Fittings	0.4	40mm polyester fibre insulation (250g/m ²) – or similar

*Note: Total minimum R-Value for ductworks can be reduced by 0.5 if the ducts are located under a suspended floor with enclosed perimeter or in a roof space that has insulation of not less than R0.5 directly located beneath the roofing

6.5. Artificial Lighting and Power:

6.5.1.1. As no electrical design showing the relevant lighting wattage has been provided part 3.12.5. An alternative assessment has been undertaken and indicates that the development must be restricted to the below nominated watts per meter for each area.

All external perimeter lighting must be installed as per the following specifications;

(i) be controlled by—

- (A) a daylight sensor; or
- (B) a time switch that is capable of switching on and off electric power to the system at variable pre-programmed times and on variable pre-programmed days; and
- (C) have an average light source efficacy of not less than 60 Lumens/W; or
- (D) be controlled by a motion detector; and

(ii) when used for decorative purposes, such as facade lighting or signage lighting, have a separate time switch.


Artificial lighting and power is to be limited throughout the residential apartments, as a sufficient electrical design has not been provided, table and diagram below indicating the required maximum wattages to be adhered to.

This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.


The logo consists of the letters 'G' and 'S' joined together in a bold, black, serif font.

SPACES	MAXIMUM WATTS PER METER	AREA
Residential Areas	4.4 W/m ² (Reduced 20% from BCA allowance)	
Garage	2.4 W/m ² (Reduced 20% from BCA allowance)	
Balcony/ Veranda	3.2 W/m ² (Reduced 20% from BCA allowance)	

GROUND FLOORPLAN



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987. The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.



6.5..1.2. The following table is an overview to the NatHERS energy rating assessment undertaken using FirstRate assessment software for whole buildings.

Building	Star Rating	Heating Loads (MJ/m ²)	Cooling Loads (MJ/m ²)	Energy Consumption (MJ/m ²)
Dwelling 1	6.1	100	21.2	121.2
Dwelling 2	6.3	91.9	21.3	113.2
Dwelling 3	6.3	99.2	16.1	115.3
Dwelling 4	6.2	101.1	15.4	116.5
Average	6.2	98.05	18.5	116.5

BESS Assessment

6.6..1.1. BESS assessment has been undertaken and prior to compliance of these requirements the following items must be actioned or shown on drawings

Items	Status	Who to Action	Remark
External lighting sensors annotated	Incomplete	Architect Electrical Engineer	Make a note / Show external lighting sensors
Location of any stormwater management systems used in STORM and rainwater tanks	Incomplete	Architect Civil Engineer	Show permeable concrete required as part of STORM rating, must be engineered by civil engineer A minimum 2500L water tank installed to each



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

Water efficient garden annotated

Incomplete

Architect

house (100% of roof to discharge into tanks), toilets and laundries to be connected to the tanks.

Glazing specification to be annotated

Incomplete

Architect

Drawings to be amended to nominate usage of only low water use plant selection and specify water efficient irrigation (i.e. drip irrigation with timers and rain sensors)

Show window and glazing specification as per this report

6.6..1.2. The following table is an overview to the BESS assessment which gave this project a score of 57% out of 100%:

Management (33% Score)

2.2

Thermal Performance Modelling (Multi-Dwelling Residential) –

Preliminary NatHERS ratings have been undertaken, it has demonstrated that townhouses will be achieving a minimum star rating of 6.0 stars.

Water (66% Score)

Water Approach –

Water approach has been assessed using the BESS built in calculation tools.

Water Profile Questions –

As part of this project a 2,500litre rainwater tank will be installed to each townhouse. A total of approximate 364square meters of roof area will be connected to the rainwater tanks.

Water fixtures, fittings and connections –

The following fixtures and fittings are to be installed;

- Showerheads = 4 Star WELS (>6.0 but <=7.5)
- Kitchen Taps = 5 Star WELS
- Bathroom Taps = 5 Star WELS
- WC = 3 Star WELS
- Rainwater Tank = All toilets and laundries are to be connected to the rainwater tank

1.1

Potable Water Use Reduction (Interior Uses) –

BESS assessment tool has calculated a credit of 40% for this section.

2.1

Rainwater Collection & Reuse –

BESS assessment tool has calculated a credit of 100% for this section.

3.1

Water Efficient Landscaping –

BESS assessment tool has calculated a credit of 100% for this section.

Plants to be installed that use low water use plant selection, water efficient irrigation such as drip irrigation with timers and rain sensors.

Energy (50% Score)

Energy Approach –

The BESS build in calculation tools have been used to approach the energy section.

Energy Profile Questions –

No gas supply will be installed, development will be wholly all-electric.



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

Dwelling Energy -

The information must not be used for any other purpose. By taking a copy of this document

installed:

you acknowledge and agree that you will only

use the document for the purpose specified above

and that any dissemination, distribution or copying

of this document is strictly prohibited.

- NATHERS ratings = All Townhouses will achieve an average of 6.0 stars

- Type of Heating = Reverse cycled central heating, achieving efficiency of 4 stars

- Type of Cooling = Refrigerate central, achieving efficiency of 4 stars

- Type of Hot Water System = Electric Heat Pump Band 2

- Clothes Line = Private outdoor clotheslines

2.1 Greenhouse Gas Emissions –

BESS assessment tool has calculated a credit of 100% for this section.

2.3 Electricity Consumption –

BESS assessment tool has calculated a credit of 100% for this section.

2.4 Gas Consumption –

BESS assessment tool has calculated a credit of 100% for this section.

2.6 Electrification –

BESS assessment tool has calculated a credit of 100% for this section.

3.2 Hot Water –

BESS assessment tool has calculated a credit of 100% for this section.

3.3 External Lighting –

BESS assessment tool has calculated a credit of 100% for this section, external lighting will be controlled by a motion detector.

3.4 Clothes Drying –

BESS assessment tool has calculated a credit of 100% for this section.

Each building will be provided with Private Outdoor clothes line approximately 700mm x 1200mm in area.

3.6 Internal Lighting (Residential Multiple Dwelling) –

The W/m² of illumination power density will be limited to be 20% lower than as that required under NCC/BCA. Development will achieve a maximum illumination power density of 4W/sqm or less will be achieved.

BESS assessment tool has calculated a credit of 100% for this section.

3.7 Internal Lighting (Non-Residential) –

The W/m² of illumination power density will be limited to be 20% lower than as that required under NCC/BCA.

BESS assessment tool has calculated a credit of 100% for this section.

This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

Stormwater (100% Score)

Stormwater Treatment

11 Melbourne Water STORM rating has been undertaken achieving a score rating of 101%.


A minimum combined roof area of 364m² (100% of roof area) must be connected to a 2500litre water tanks to each dwelling. All toilets and laundries are to be connected to the water tanks. For

STORM rating please see appendix 4.

Water tank Design

Unit 3

79m² or 100% of the roof space to discharge into a 2500L watertank



Unit 1

103m² or 100% of the roof space to discharge into a 2500L watertank

Unit 3

79m² or 100% of the roof space to discharge into a 2500L watertank

Unit 2

103m² or 100% of the roof space to discharge into a 2500L watertank

Indoor Environment Quality (60% Score)

3.1

Thermal Comfort- Double Glazing –

BESS assessment tool has calculated a credit of 100% for this section.

All townhouses will be installed with double glazing to all bedrooms and living areas.

Paints

Proposed design principals must ensure that adequate natural lighting and ventilation will be provided to all habitable rooms in accordance with the requirements of the BCA. Development commits that all paints and internal finishes are selected based on low Volatile Organic Compounds (VOCs), this will ensure that building occupants are exposed to low toxicity materials.



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

Transport (50% Score)

1.1 **Bicycle Parking (Residential) –**
BESS assessment tool has calculated a credit of 100% for this section.

Townhouses will be provided 4 bicycle parking spaces as required, 1 per town house.

Waste (50% Score)

2.1 Operational Waste (Food & Garden Waste) –

BESS assessment tool has calculated a credit of 100% for this section as facilities will be provided for onsite management of food and garden waste, such as composting bins.

Urban Ecology (62% Score)

2.1 Vegetation –

BESS assessment tool has calculated a credit of 100% for this section as the site is covered with 33% vegetation.

3.1 Food Production (Residential) –

BESS assessment tool has calculated a credit of 0% for this section.

Innovation

1.1 Innovation –

BESS assessment tool has calculated a credit of 0% as we are not seeking any innovation credits.

6.6.1.3. Urban Ecology

As part of proposed construction works, only indigenous vegetation will be planted to buildings gardens and surrounding lands. During time of construction, special care will be taken by building contractors to ensure that contamination from products such as concrete, paint, adhesives etc to land is minimised by placing special bins and wash-up areas.

6.6.1.4. Sustainable Materials

Development will be committed to using either of the following sustainable materials;

- Supplementary Cementing Material (SCMs) with all Portland cement are to be used for building footing and driveway construction, or
- All timber used in construction must be either PEFC or FSC sustainable certified timers.

Drawings are to be amended to note the above commitment and it will be the builders responsibility to ensure the commitments are met.

7. CONCLUSION

- 7.1. An assessment of the proposed works has shown that the works will achieve an overall rating of 6.0 stars. All insulation requirements are to be as nominated in the FirstRate report with additional insulation and as per clause 6.1 of this report.

The BESS assessment concludes that the proposed new development will achieve a score of 54% out of 100%.

Any alteration or variations to the proposed building fabric, window schedules and building form could detriment the star rating and BESS outcomes, and further reassessment may need to be conducted.



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

Appendix 1 – Sustainable Management Plan

This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.


The information must not be used for any other purpose. By taking a copy of this document

you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

This BESS report outlines the sustainable design commitments of the proposed development at 8 Carpenter St Noble Park Victoria 3174. The BESS report and accompanying documents and evidence are submitted in response to the requirement for a Sustainable Design Assessment or Sustainability Management Plan at Greater Dandenong City Council.

Note that where a Sustainability Management Plan is required, the BESS report must be accompanied by a report that further demonstrates the development's potential to achieve the relevant environmental performance outcomes and documents the means by which the performance outcomes can be achieved.

Your BESS Score



54%


Project details

Address	8 Carpenter St Noble Park Victoria 3174
Project no	BA9F5D93-R1
BESS Version	BESS-7
Site type	Multi dwelling (dual occupancy, townhouse, villa unit etc)
Account	geokalconsult@gmail.com
Application no.	
Site area	902.00 m ²
Building floor area	602.00 m ²
Date	22 January 2024
Software version	1.8.1-B.407



Performance by category

● Your development ● Maximum available





This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

Dwellings

Name	Quantity	Area	% of total area
Townhouse			
Townhouse 1 & 2	2	167 m ²	55%
Townhouse 3 & 4	2	134 m ²	44%
Total	4	602 m²	100%

Supporting information

Floorplans & elevation notes


Credit	Requirement	Response	Status
Water 3.1	Annotation: Water efficient garden details		-
Energy 3.3	Annotation: External lighting controlled by motion sensors		-
Energy 3.4	Location of clothes line (if proposed)		-
Stormwater 1.1	Location of any stormwater management systems (rainwater tanks, raingardens, buffer strips)		-
IEQ 3.1	Annotation: Glazing specification (U-value, SHGC)		-
IEQ 3.3	North-facing living areas		-
Transport 1.1	Location of residential bicycle parking spaces		-
Waste 2.1	Location of food and garden waste facilities		-
Urban Ecology 2.1	Location and size of vegetated areas		-

Supporting evidence

Credit	Requirement	Response	Status
Management 2.2	Preliminary NatHERS assessments		-
Energy 3.5	Average lighting power density and lighting type(s) to be used		-
Stormwater 1.1	STORM report or MUSIC model		-
IEQ 3.1	Reference to floor plans or energy modelling showing the glazing specification (U-value and Solar Heat Gain Coefficient, SHGC)		-
IEQ 3.3	Reference to the floor plans showing living areas orientated to the north		-

Credit summary

Management Overall contribution 4.5%





This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.


The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

BESS, 304 Queen Street, Park View, South Australia 5000, Noble Park...


Water Overall contribution 9.0%

1.1 Portable Water Use Production

3.1 Water Efficient Landscaping




Energy Overall contribution 27.5%



Stormwater Overall contribution 13.5%



IEQ Overall contribution 16.5%





This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document

Transport Overall contribution 9.0%

you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.




N/A Scoped Out


Not enough dwellings.



Waste Overall contribution 5.5%



Urban Ecology Overall contribution 5.5%



Innovation Overall contribution 9.0%



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987. The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

1.1 Pre-Application Meeting		0%
Score Contribution	This credit contributes 50.0% towards the category score.	
Criteria	Has an ESD professional been engaged to provide sustainability advice from schematic design to construction? AND Has the ESD professional been involved in a pre-application meeting with Council?	
Question	Criteria Achieved ?	
Project	No	
2.2 Thermal Performance Modelling - Multi-Dwelling		100%
Residential		
Score Contribution	This credit contributes 33.3% towards the category score.	
Criteria	Have preliminary NATHERS ratings been undertaken for all thermally unique dwellings?	
Question	Criteria Achieved ?	
Townhouse	Yes	
4.1 Building Users Guide		0%
Score Contribution	This credit contributes 16.7% towards the category score.	
Criteria	Will a building users guide be produced and issued to occupants?	
Question	Criteria Achieved ?	
Project	No	



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document

you acknowledge and agree that you will only

use the document for the purpose specified above

and that any dissemination, distribution or copying

of this document is strictly prohibited.

BESS, 30 Quay Street, Hobart, Tasmania, 7000, Australia, 03 6230 1000, 03 6230 1050...

Water Profile Question

Water Use Calculations

Water Approach

Use the built in calculation tools

Project Water Profile Question

Do you have a reticulated third pipe or an on-site water recycling system?: No

Are you installing a swimming pool?: No

Are you installing a rainwater tank?: Yes

Water fixtures, fittings and connections

Showerhead: All 4 Star WELS (>= 6.0 but <= 7.5)

Bath: All Scope out

Kitchen Taps: All >= 5 Star WELS rating

Bathroom Taps: All >= 5 Star WELS rating

Dishwashers: All Default or unrated

WC: All >= 3 Star WELS rating

Urinals: All Scope out

Washing Machine Water Efficiency: All Occupant to Install

Which non-potable water source is the dwelling/space connected to?:

Townhouse 1 & 2 Tanks 1-2

Townhouse 3 & 4 Tanks 3-4

Non-potable water source connected to Toilets: All Yes

Non-potable water source connected to Laundry (washing machine): All Yes

Non-potable water source connected to Hot Water System: All No

Rainwater Tanks

What is the total roof area connected to the rainwater tank?:

Tanks 1-2 206 m²

Tanks 3-4 158 m²

Tank Size:

Tanks 1-2 5,000 Litres

Tanks 3-4 5,000 Litres

Irrigation area connected to tank:

Tanks 1-2 -

Tanks 3-4 -

Is connected irrigation area a water efficient garden?:

Tanks 1-2 Yes

Tanks 3-4 Yes

Other external water demand connected to tank?:

Tanks 1-2 -

Tanks 3-4 -



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document

1.1 Potable Water Use Reduction
Score Contribution This credit contributes 83.3% towards the category score.
Criteria What is the reduction in total potable water use due to efficient fixtures, appliances, rainwater use and recycled water use? To achieve points in this credit there must be >25% potable water reduction.
Question Output Reference
Project 719 kL
Output Proposed (excluding rainwater and recycled water use)
Project 602 kL
Output Proposed (including rainwater and recycled water use)
Project 387 kL
Output % Reduction in Potable Water Consumption
Project 46 %
Output % of connected demand met by rainwater
Project 99 %
Output How often does the tank overflow?
Project Often
Output Opportunity for additional rainwater connection
Project 144 kL

60%

3.1 Water Efficient Landscaping 100%

Score Contribution	This credit contributes 16.7% towards the category score.
Criteria	Will water efficient landscaping be installed?
Question	Criteria Achieved ?
Project	Yes



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document

you acknowledge and agree that you will only

use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

Score Contribution

This credit contributes 5.0% towards the category score.

Criteria

What is the % reduction in the instantaneous (peak-hour) demand against the benchmark?

Output Peak Thermal Cooling Load - Baseline

Townhouse 51.4 kW

Output Peak Thermal Cooling Load - Proposed

Townhouse 51.5 kW

Output Peak Thermal Cooling Load - % Reduction

Townhouse -1 %

2.2 Peak Demand

0%

Score Contribution

This credit contributes 5.0% towards the category score.

Criteria

What is the % reduction in annual electricity consumption against the benchmark?

2.3 Electricity Consumption

100%

Score Contribution

This credit contributes 10.0% towards the category score.

Criteria

What is the % reduction in annual electricity consumption against the benchmark?

Output Reference

Townhouse 40,772 kWh

Output Proposed

Townhouse 10,895 kWh

Output Improvement

Townhouse 73 %

2.4 Gas Consumption

N/A Scoped Out

This credit was scoped out

No gas connection in use

2.5 Wood Consumption

N/A Scoped Out

This credit was scoped out

No wood heating system present

2.6 Electrification

100%

Score Contribution

This credit contributes 10.0% towards the category score.

Criteria

Is the development all-electric?

Question

Criteria Achieved?

Project Yes

3.2 Hot Water

100%

Score Contribution

This credit contributes 5.0% towards the category score.

Criteria

What is the % reduction in annual energy consumption (gas and electricity) of the hot water system against the benchmark?

Output Reference

Townhouse 53,434 MJ

Output Proposed

Townhouse 12,783 MJ

Output Improvement

Townhouse 76 %



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document

you acknowledge and agree that you will only

use the document for the purpose specified above and that any dissemination, distribution or copying

of this document is strictly prohibited.

BESS, 3 Copeland Street, Park View, South Australia 5000, St. Noble Par...

2.3 External lighting	100%
Score Contribution This credit contributes 5.0% towards the category score.	
Criteria The external lighting controlled by a motion detector?	
Question	Criteria Achieved ?
Townhouse	Yes
3.4 Clothes Drying	100%
Score Contribution	This credit contributes 5.0% towards the category score.
Criteria	What is the % reduction in annual energy consumption (gas and electricity) from a combination of clothes lines and efficient driers against the benchmark?
Output	Reference
Townhouse	2,690 kWh
Output	Proposed
Townhouse	538 kWh
Output	Improvement
Townhouse	80 %
3.5 Internal Lighting - Houses and Townhouses	100%
Score Contribution	This credit contributes 5.0% towards the category score.
Criteria	Does the development achieve a maximum illumination power density of 4W/sqm or less?
Question	Criteria Achieved?
Townhouse	Yes
4.4 Renewable Energy Systems - Other	0% <input checked="" type="checkbox"/> Disabled
This credit is disabled	No other (non-solar PV) renewable energy is in use.
4.5 Solar PV - Houses and Townhouses	0% <input checked="" type="checkbox"/> Disabled
This credit is disabled	No solar PV renewable energy is in use.

Stormwater Overall contribution 14% Minimum required 100%

Which stormwater modelling are you using?:	Melbourne Water STORM tool
1.1 Stormwater Treatment 100%	
Score Contribution	This credit contributes 100.0% towards the category score.
Criteria	Has best practice stormwater management been demonstrated?
Question	STORM score achieved
Project	101
Output	Min STORM Score
Project	100



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

BESS, 304 Parklands Drive, Park View, Durban, 4301, South Africa. Telephone: +27 31 507 1000, Email: info@bess.net.au, Website: www.bess.net.au

100% of the credit towards this category is available.

2.2 Cross Flow Ventilation

0%

Score Contribution This credit contributes 20.0% towards the category score.

Criteria	Are all habitable rooms designed to achieve natural cross flow ventilation?
Question	Criteria Achieved ?
Townhouse	No

3.1 Thermal comfort - Double Glazing

100%

Score Contribution This credit contributes 40.0% towards the category score.

Criteria	Is double glazing (or better) used to all habitable areas?
Question	Criteria Achieved ?
Townhouse	Yes

3.2 Thermal Comfort - External Shading

0%

Score Contribution This credit contributes 20.0% towards the category score.

Criteria	Is appropriate external shading provided to east, west and north facing glazing?
Question	Criteria Achieved ?
Townhouse	No

3.3 Thermal Comfort - Orientation

100%

Score Contribution This credit contributes 20.0% towards the category score.

Criteria	Are at least 50% of living areas orientated to the north?
Question	Criteria Achieved ?
Townhouse	Yes

Transport Overall contribution 4%

1.1 Bicycle Parking - Residential	100%
Score Contribution	This credit contributes 50.0% towards the category score.

Criteria	How many secure and undercover bicycle spaces are there per dwelling for residents?
Question	Bicycle Spaces Provided ?
Townhouse	4
Output	Min Bicycle Spaces Required
Townhouse	4

1.2 Bicycle Parking - Residential Visitor	N/A	❖ Scoped Out
This credit was scoped out	Not enough dwellings.	

2.1 Electric Vehicle Infrastructure	0%
Score Contribution	This credit contributes 50.0% towards the category score.
Criteria	Are facilities provided for the charging of electric vehicles?
Question	Criteria Achieved ?
Project	No



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document

Waste
you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

Score Contribution

This credit contributes 50.0% towards the category score.

0%

Criteria

If the development is on a site that has been previously developed, has at least 30% of the existing building been re-used?

Question

Criteria Achieved ?

Project

No

2.1 - Operational Waste - Food & Garden Waste

100%

Score Contribution

This credit contributes 50.0% towards the category score.

Criteria

Are facilities provided for on-site management of food and garden waste?

Question

Criteria Achieved ?

Project

Yes



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

BESS, 3 Cupperton, Mullumbimby NSW 2325, Australia, 1000 St, Noble Park...

Score Contribution	100%
Criteria	How much of the site is covered with vegetation, expressed as a percentage of the total site area?
Question	Percentage Achieved ?
Project	41 %
2.1 Vegetation	0%
Score Contribution	This credit contributes 50.0% towards the category score.
Criteria	Does the development incorporate a green roof?
Question	Criteria Achieved ?
Project	No
2.2 Green Roofs	0%
Score Contribution	This credit contributes 12.5% towards the category score.
Criteria	Does the development incorporate a green wall or green façade?
Question	Criteria Achieved ?
Project	No
2.3 Green Walls and Facades	0%
Score Contribution	This credit contributes 12.5% towards the category score.
Criteria	Is there a tap and floor waste on every balcony / in every courtyard?
Question	Criteria Achieved ?
Townhouse	No
2.4 Private Open Space - Balcony / Courtyard Ecology	0%
Score Contribution	This credit contributes 12.5% towards the category score.
Criteria	What area of space per resident is dedicated to food production?
Question	Food Production Area
Townhouse	-
Output	Min Food Production Area
Townhouse	3 m ²
3.1 Food Production - Residential	0%
Score Contribution	This credit contributes 12.5% towards the category score.
Criteria	What percentage of the Innovation points have been claimed (10 points maximum)?
Question	
Townhouse	

Innovation Overall contribution 0%

1.1 Innovation	0%
Score Contribution	This credit contributes 100.0% towards the category score.
Criteria	What percentage of the Innovation points have been claimed (10 points maximum)?

Disclaimer

The Built Environment Sustainability Scorecard (BESS) has been provided for the purpose of information and communication. While we make every effort to ensure that material is accurate and up to date (except where denoted as 'archival'), this material does in no way constitute the provision of professional or specific advice. You should seek appropriate, independent, professional advice before acting on any of the areas covered by BESS.



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other

BESS, 6 Napier Street, Frankston VIC 3199, Australia. Tel: 03 8540 1000, Fax: 03 8540 1001, Email: info@bess.net.au

The Municipal Association of Victoria (MAV) and CASBE (Council Alliance for a Sustainable Built Environment) member councils do not guarantee, and

accept no legal liability whatsoever arising from or connected to, the accuracy, reliability, currency or completeness of BESS, any material contained on

this website or any linked sites.

use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

Appendix 2 – FirstRate Ratings

This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987. The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

Generated on 23 Jan 2024 using FirstRate5: 5.3.2b (3.21)

Property

Address 1, 8 Carpenter Street, Noble Park, VIC, 3174
Lot/DP -
NCC Class* Class 1a
Type New Home

Plans

Main plan 9/01/2024
Prepared by KX Architecture Pty Ltd

Construction and environment

Assessed floor area (m ²)*	Exposure type
Conditioned*	suburban
Unconditioned*	NatHERS climate zone
Total	62 Moorabbin Airport
Garage	



Accredited assessor

Name George Kalajdzic
Business name Geokal Services Pty Ltd
Email geokalconsult@gmail.com
Phone 0431631535
Accreditation No. DMN/11/2035
Assessor Accrediting Organisation Design Matters National
Declaration of interest Declaration completed: no conflicts

National Construction Code (NCC) requirements

The NCC's requirements for NatHERS-rated houses are detailed in 3.12.0(a)(i) and 3.12.5 of the NCC Volume Two. For apartments the requirements are detailed in J0.2 and J5 to J8 of the NCC Volume One.

In NCC 2018, these requirements include minimum star ratings and separate heating and cooling load limits that need to be met by buildings and apartments through the NatHERS assessment. Requirements additional to the NatHERS assessment that must also be satisfied include, but are not limited to, insulation installation methods, thermal breaks, building sealing, water heating and pumping, and artificial lighting requirements. The NCC and NatHERS Heating and Cooling Load Limits (Australian Building Codes Board Standard) are available at www.abcb.gov.au.

State and territory variations and additions to the NCC may also apply.

* Refer to glossary.

Generated on 23 Jan 2024 using FirstRate5: 5.3.2b (3.21) for U 1, 8 Carpenter Street, Noble Park,



Thermal performance

Heating	Cooling
100 MJ/m ²	21.2 MJ/m ²

About the rating

NatHERS software models the expected thermal energy loads using information about the design and construction, climate and common patterns of household use. The software does not take into account appliances, apart from the airflow impacts from ceiling fans.

Verification

To verify this certificate, scan the QR code or visit [When using either link, ensure you are visiting www.FR5.com.au.](http://www.FR5.com.au)

This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

Generated on 23 Jan 2024 using FirstRate5: 5.3.2b (3.21)

Property

Address	2, 8 Carpenter Street, Noble Park, VIC, 3174
Lot/DP	-
NCC Class*	Class 1a
Type	New Home

Plans

Main plan	9/01/2024
Prepared by	KX Architecture Pty Ltd

Construction and environment

Assessed floor area (m ²)*	Exposure type
Conditioned*	suburban
Unconditioned*	NatHERS climate zone
Total	62 Moorabbin Airport
Garage	



Accredited assessor

Name	George Kalajdzic
Business name	Geokal Services Pty Ltd
Email	geokalconsult@gmail.com
Phone	0431631535
Accreditation No.	DMN/11/2035
Assessor Accrediting Organisation	
Design Matters National	
Declaration of interest	Declaration completed: no conflicts

National Construction Code (NCC) requirements

The NCC's requirements for NatHERS-rated houses are detailed in 3.12.0(a)(i) and 3.12.5 of the NCC Volume Two. For apartments the requirements are detailed in J0.2 and J5 to J8 of the NCC Volume One.

In NCC 2018, these requirements include minimum star ratings and separate heating and cooling load limits that need to be met by buildings and apartments through the NatHERS assessment. Requirements additional to the NatHERS assessment that must also be satisfied include, but are not limited to, insulation installation methods, thermal breaks, building sealing, water heating and pumping, and artificial lighting requirements. The NCC and NatHERS Heating and Cooling Load Limits (Australian Building Codes Board Standard) are available at www.abcb.gov.au.

State and territory variations and additions to the NCC may also apply.

* Refer to glossary.

Generated on 23 Jan 2024 using FirstRate5: 5.3.2b (3.21) for U 2, 8 Carpenter Street, Noble Park,



Thermal performance

Heating	Cooling
91.9 MJ/m ²	21.3 MJ/m ²

About the rating

NatHERS software models the expected thermal energy loads using information about the design and construction, climate and common patterns of household use. The software does not take into account appliances, apart from the airflow impacts from ceiling fans.

Verification

To verify this certificate, scan the QR code or visit www.FR5.com.au. When using either link, ensure you are visiting www.FR5.com.au.

This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

National House Energy Rating Scheme

NatHERS Certificate

Generated on 23 Jan 2024 using FirstRate5: 5.3.2b (3.21)

Property

Address 3, 8 Carpenter Street, Noble Park, VIC, 3174
Lot/DP -
NCC Class* Class 1a
Type New Home

Plans

Main plan 9/01/2024
Prepared by KX Architecture Pty Ltd

Construction and environment

Assessed floor area (m ²)*	Exposure type
Conditioned*	suburban
Unconditioned*	NatHERS climate zone
Total	62 Moorabbin Airport
Garage	



Accredited assessor

Name George Kalajdzic
Business name Geokal Services Pty Ltd
Email geokalconsult@gmail.com
Phone 0431631535
Accreditation No. DMN/11/2035
Assessor Accrediting Organisation Design Matters National
Declaration of interest Declaration completed: no conflicts



Thermal performance

Heating	Cooling
99.2 MJ/m ²	16.1 MJ/m ²

About the rating

NatHERS software models the expected thermal energy loads using information about the design and construction, climate and common patterns of household use. The software does not take into account appliances, apart from the airflow impacts from ceiling fans.

Verification

To verify this certificate, scan the QR code or visit [When using either link, ensure you are visiting www.FR5.com.au.](http://www.FR5.com.au)

National Construction Code (NCC) requirements

The NCC's requirements for NatHERS-rated houses are detailed in 3.12.0(a)(i) and 3.12.5 of the NCC Volume Two. For apartments the requirements are detailed in J0.2 and J5 to J8 of the NCC Volume One.

In NCC 2019, these requirements include minimum star ratings and separate heating and cooling load limits that need to be met by buildings and apartments through the NatHERS assessment. Requirements additional to the NatHERS assessment that must also be satisfied include, but are not limited to, insulation installation methods, thermal breaks, building sealing, water heating and pumping, and artificial lighting requirements. The NCC and NatHERS Heating and Cooling Load Limits (Australian Building Codes Board Standard) are available at www.abcb.gov.au.

State and territory variations and additions to the NCC may also apply.

* Refer to glossary.

This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987. The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

Generated on 23 Jan 2024 using FirstRate5: 5.3.2b (3.21)

Property

Address 4, 8 Carpenter Street, Noble Park, VIC, 3174
Lot/DP -
NCC Class* Class 1a
Type New Home

Plans

Main plan 9/01/2024
Prepared by KX Architecture Pty Ltd

Construction and environment

Assessed floor area (m²)*	Exposure type
Conditioned*	suburban
Unconditioned*	NatHERS climate zone
Total	62 Moorabbin Airport
Garage	



Accredited assessor

Name George Kalajdzic
Business name Geokal Services Pty Ltd
Email geokalconsult@gmail.com
Phone 0431631535
Accreditation No. DMN/11/2035
Assessor Accrediting Organisation Design Matters National
Declaration of interest Declaration completed: no conflicts

National Construction Code (NCC) requirements


The NCC's requirements for NatHERS-rated houses are detailed in 3.12.0(a)(i) and 3.12.5 of the NCC Volume Two. For apartments the requirements are detailed in J0.2 and J5 to J8 of the NCC Volume One.

In NCC 2019, these requirements include minimum star ratings and separate heating and cooling load limits that need to be met by buildings and apartments through the NatHERS assessment. Requirements additional to the NatHERS assessment that must also be satisfied include, but are not limited to, insulation installation methods, thermal breaks, building sealing, water heating and pumping, and artificial lighting requirements. The NCC and NatHERS Heating and Cooling Load Limits (Australian Building Codes Board Standard) are available at www.abcb.gov.au.

State and territory variations and additions to the NCC may also apply.

* Refer to glossary.

Generated on 23 Jan 2024 using FirstRate5: 5.3.2b (3.21) for U 4, 8 Carpenter Street, Noble Park,





This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

Appendix 3 – STORM Rating & Selection of Plants



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987. The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

Melbourne Water STORM Rating Report

TransactionID: 0
Municipality: GREATER DANDENONG
Rainfall Station: GREATER DANDENONG
Address: 8 Carpenter Street

Noble Park
VIC 3174

Assessor: George Kalajdzic
Development Type: Residential - Multiunit
Allotment Site (m2): 902.00
STORM Rating %: 101

Description	Impervious Area (m2)	Treatment Type	Treatment Area/Volume (m2 or L)	Occupants / Number Of Bedrooms	Treatment %	Tank Water Supply Reliability (%)
Unit 1 - Treated	103.00	Rainwater Tank	2,500.00	4	140.40	84.00
Unit 2 - Treated	103.00	Rainwater Tank	2,500.00	4	140.40	84.00
Unit 3 - Treated	79.00	Rainwater Tank	2,500.00	3	151.30	87.60
Unit 4 - Treated	79.00	Rainwater Tank	2,500.00	3	151.30	87.60
Driveway	137.00	None	0.00	0	0.00	0.00
Shed	24.00	None	0.00	0	0.00	0.00

This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only

use the information for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

The following selection of plants can be planted in the rain garden, builder/client can decide on plant selection during construction of rain garden.

Selection of Plants	Botanical name	Common name	Conditions	SIZE (H x W) (cm)	Picture
<i>Amigozanthos</i> sp.	Kangaroo Paw	Purpuun		30-90 x 100-120	
<i>Blechnum nudum</i>	Fishbone Water-fern		Full sun to partial shade	50-100 x 40-80	
<i>Calocephalus lacteus</i>	Milky Beauty-Heads		Full sun to partial shade	15-30 x 10-30	
<i>Carex appressa</i>	Tall Sedge		Full sun to partial shade	80-100 x 120	
<i>Carpobrotus modestus</i>	Pigface		Full sun	20cm high and spreading	

This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987. The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

<i>Chrysocephalum apiculatum</i>	Common Everlasting	Full sun	30-90 x 10-30	
<i>Derwentia perfoliata</i>	Digger's Speedwell	Full sun to partial shade	20-40 x 30-60	
<i>Dianella species</i>	–	Full sun to partial shade	60-120 x 40-150	
<i>Ficinia nodosa</i>	Knobby Club-Rush	Full sun	50-150 x 60-200	
<i>Juncas amabilis</i>	Hollow Rush	Full sun to partial shade	20-120 x 20-50	
<i>Juncas flavidus</i>	Yellow Rush	Full sun to partial shade	40-120 x 20-100	

This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987. The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

<i>Leucophyta brownii</i>	Cushion Bush	Full sun, salt tolerant	100 x 200	
<i>Lomandra species</i>	–	Full sun to partial shade	60-120 x 50-100	
<i>Melaleuca ericifolia</i>	Swamp Paperbark	Full sun to partial shade	4m high x 3m wide	
<i>Myoporum parvifolium</i>	Creeping Boobialla	Full sun	20-30 x 300	
<i>Patersonia occidentalis</i>	Native Iris	Sun to partial shade	20-40 x 30-60	

This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987. The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

<i>Pratia perfoliata</i>	Matter Pratia	Partial shade	50-150 x 1.8-5	
Wahlenbergia communis	Tufted Bluebell	Full sun	15-50 x 15	



This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

Appendix 4 – Additional Construction Consideration

This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document

Insulation you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.


A building cannot achieve energy efficiency if insulation is not adequately installed during the construction stages of the building; insulation in the ceiling can save up to 45% on heating and cooling energy costs, while insulating walls will save up to 20% on heating and cooling. The following are some installation tips that are to be adhered to when installing insulation.

Bulk Insulation

There are many different bulk insulation products circulating on today's markets, the most common of these are Glasswool (fibreglass) batts, Polyester Batts, Cellulose Fibre, Polystyrene foam Boards, Wool, Rockwool etc.

As bulk insulation functions by trapping air pockets, it is very important that insulation installers fit bulk insulation by;

- Covering all Roof and Wall spaces, and
- Trimming batts to fit tight areas around doors and windows (i.e. between Jack and Jamb studs work, between lintels and plasterboard etc), and
- Tight fitting trimming around service penetrations, and
- Adequate fittings around the suitable restraints used on recessed downlight – where possible it is recommended that Surface Mounted downlights are used as they will minimise the amount of penetrations through ceiling insulation, thus increase insulation performance, and
- Adequately providing insulation with suitable a vapour barrier. Moisture will not only reduce insulation performance, but it will also present a health problem over time, and
- Ensuring that insulation is NOT COMPRESSED as it will reduce the overall R-Value, etc.



Reflective Foils

Reflective foil insulation (also known as sisilation) is most commonly used in construction as a vapour barrier. Installers of reflective foils (usually builders or bricklayers) must be aware that reflective foils play an important role in thermal performance of a building.


The reflective 'shiny' side of a foil blocks out radiant heat from coming in or escaping out of a building depending on how it is installed. In a cold Melbourne climate, a building should always be constructed to try and keep heat in, thus the

This document has been copied and made available for the purpose of the planning process as set out in the Planning and Environment Act 1987.

The information must not be used for any other purpose. By taking a copy of this document you acknowledge and agree that you will only use the document for the purpose specified above and that any dissemination, distribution or copying of this document is strictly prohibited.

reflective shiny side should always face into the building. The following are some important facts that are to be remembered when installing reflective foil:

- Foils must overlap at least 150mm over each other and adequately taped using heavy duty tape, and
- All housewrap and building paper must be punched and taped over, and
- The shiny side of foil is to be clean and bright, dirty foils will lose the value of their thermal performance properties, and
- Ensure that there is at least 25mm of clear airspace between any building element and the 'shiny' side of reflective insulation to achieve optimum thermal performance, and
- The entire house is to be sealed with reflective foils – NOTE: Plywood bracing is not the same as reflective foil and should not to be considered as an adequate insulation or as a moisture barrier, foils are to overlap all plywood bracing, etc.



Sealing

Gaps in building are mostly responsible for the majority of air infiltration. Gaps between floor joist, windows and doors, roof tiles, bearers and joist account for the most air infiltration into a building. The following are places that are to be sealed either with self expanding foam or similar during the construction stages to stop air infiltration;

- Between external door frames and enclosing timber framing, and
- Between external window frames and enclosing timber framing, etc.

To addition of the above mentioned sealing the following must be implemented;

- All external exhaust fans such as bathrooms, laundries and toilets are to be provided with self-closing dampers, and
- All mechanical air-conditioning and heating vents are to be provided with self-closing dampers, and
- Doors are to be provided with seals that will stop air-leaking from beneath and around the doors, and
- Windows are to be provided with seals that will stop air-leaking from beneath and around the windows, etc.
-